







مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 PSD81602-A360	<p>8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera                      Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS                      5mm fixed lens                      PTZ: One 1/1.9" 2Megapixel progressive scan CMOS                      5.5mm~206mm, 37x optical zoom                      H.265+/H.265/H.264+/H.264 triple-stream encoding                      2x25fps@4096x1800+50/60fps@1080P                      Support 360-degree panoramic view                      WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC                      Smart tracking, Intelligent Function(Tripwire, Intrusion)                      2/1 channel Audio In/Out, 7/2 channel Alarm In/Out                      RS485, Micro SD memory, IP67, IK10</p>		Call
2 PSD8802-A180	<p>4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera                      Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS                      5mm fixed lens                      PTZ: One 1/1.9" 2Megapixel progressive scan CMOS                      5.5mm~206mm, 37x optical zoom                      H.265+/H.265/H.264+/H.264 triple-stream encoding                      25fps@4096x1800+50/60fps@1080P                      Support 180-degree panoramic view                      WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC                      Smart tracking, Intelligent Function(Tripwire, Intrusion)                      2/1 channel Audio In/Out, 7/2 channel Alarm In/Out                      RS485, Micro SD memory, IP67, IK10</p>		Call
3 SDT4E425-4F-GB-A-PV1	<p>X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera                      Panorama: 1/2.8" 4Megapixel F1.0 CMOS                      Detail: 1/2.8" 4Megapixel STARVIS™ CMOS                      25x optical zoom, Max. 25/30fps@4M, IR distance up to 100 m                      Active deterrence, Auto tracking 3.0, Smart tracking, Perimeter protection, Smart dual light +                      Panorama: 0.001 lux@F1.0 (Color, 30 IRE); 0.0005 lux@F1.0 (B/W, 30 IRE); 0 lux (Illuminator on);                      Detail: 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on)                      FoV Panorama: H: 101° Detail: H: 51.9°, Auto Focus                      Preset 300, Tour 8, Pattern 5, Scan 5                      SMD 4.0, Quick Pick, Tripwire; intrusion; climbing fences; loitering detection; abandoned/missing object; fast moving;                      parking detection; people gathering; vehicle/human alarm classification; linking the detail camera to track objects                      Light Warning, Sound Warning                      3 Streams, H.265+, WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, RoI, EIS, Defog                      Micro SD 512GB, Audio I/O 1/1, Alarm I/O 2/1                      12VDC, PoE+, TVS 6000 V lightning proof;IP66; surge protection; voltage transient protection</p>		616,500,000
4 IPC-PFW38495-A180-AS-PV	<p>2x4MP TiOC Duo Splicing Fixed-focal Bullet WizSense Network Camera                      Dual 1/2.7" Progressive CMOS Sensor, 2.8mm Fixed Lens                      Outputs 180° ve angle splicing image, max. 8 MP (4096 × 1860)@20 fps                      H.265 codec, high compression rate, ultra-low bit rate, 3 Streams                      IR 25m, Warmlight 20m, 0.005 lux@F1.4 (Color, 30 IRE) 0.0005 lux@F1.4 (B/W, 30 IRE) 0 lux (Illuminator on)                      WDR 120db, SSA, 3D NR, HLC, BLC, AGC, AWB, 3D DNR, RoI,                      Micro SD 256GB, Audio I/O 1/1, Alarm I/O 1/1, <b>Dual Mic, Speaker, Two Way Talk</b>                      EPTZ, SMD 4.0, arm &amp; disarm option, Intrusion, tripwire, Quick Pick,                      Sound Warning, Light Warning(Red and Blue Light)                      12VDC, IP67, Metal Case</p>		256,000,000
5 IPC-EBW8842-AS	<p>8MP IR Fisheye WizMind Network Camera                      8MP 1/1.7" CMOS image sensor, low luminance, and high definition image                      Min. Illumination 0.01 Lux@F2.0 (Color, 30 IRE), 0.001 Lux@F2.0 (B/W, 30 IRE), 0 Lux (Illuminator on)                      Focal Length 1.85mm, Field of View Horizontal: 185°; Vertical: 180°                      Outputs max. 8M (3280 × 2480) @25/30 fps                      Built-in IR LED, and the max. illumination distance is 10 m                      IVS: Intrusion, tripwire, heat map, people counting, Smart Search                      DWDR, HLC, BLC, AWB, AGC, 3D DNR, RoI, Defog, ICR, SMART H.264 +/H.265+                      Built-in Dual Array Mic and Speaker, Audio in/out 1/1, Alarm in/out 2/2, Micro SD 256GB                      12V DC/PoE, IP67 and IK10 protection</p>		560,000,000
6 IPC-HFW2849T-ZAS-IL	<p>8MP Smart Dual Light Vari-focal Bullet WizSense Network Camera                      8-MP 1/2.7" Progressive CMOS, max. 8MP@20 fps/4MP@25/30fps, 2.7-13.5mm                      Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) 0.0008 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on)                      WDR 120db, 3D DNR, HLC, BLC, AWB, AGC, ROI, SMART H.264+/H.265+, Smart Dual Light 60m                      SMD+, Intrusion, Tripwire, MSD256GB, Audio I/O 1/1, A,arm I/O 1/1, Built-in Mic                      IP67, IK10, 12 VDC/PoE, Metal</p>		225,900,000
7 IPC-HFW2849T-AS-IL	<p>8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera                      8-MP 1/2.7" Progressive CMOS image sensor, 8MP(3840×2160)@20fps, (2688×1520)@25/30fps                      Min. Illumination 0.008 Lux@F1.6 (Color, 30 IRE) 0.0008 Lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)                      Illumination Distance up to 60 m (195.85 ft) (IR) up to 50 m (164.04 ft) (Warm light)                      Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate                      Intelligent monitoring: Intrusion, tripwire, SMD Plus                      RoI, WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination                      Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB                      12 VDC/PoE, IP67, IK10, Metal Case</p>		167,900,000

















<p>8 DH-IPC-HFW5449T1-ZE-LED</p>   	<p>4MP 1/1.8" CMOS image sensor, Full-color Vari-focal Warm LED Bullet WizMind Network Camera Outputs max. 4MP (2688 × 1520) @30 fps, Focal Length 2.7 mm–12 mm Min. Illumination 0.0005 Lux@F1.0 , 5/N Ratio &gt; 56 dB Built-in warm illuminator, and the max. illumination distance : 70 m ROI, SMART H.264+/H.265+, flexible coding, WDR 140db , 3D NR, HLC, BLC IVS (Perimeter Protection) : Tripwire; intrusion; fast moving, loitering detection, people gathering; parking detection, Face Detection, People Counting, Intelligent Search Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, <b>built-in Mic</b> and speaker 12V DC/PoE power supply, ePoE, IP67 protection, SMD 3.0</p>	 <p>311,000,000</p>
<p>9 HFW5442EP-ZE-0832</p>   	<p>4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688x1520), 50/60fps@2Mp(1920 × 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lens, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p>	 <p>263,200,000</p>
<p>10 IPC-HFW5541E-ZE-S3</p>    	<p>5MP IR Vari-focal Bullet WizMind Network Camera 5-MP (2960 × 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (Illuminator on 60m) 2.7 mm–13.5 mm Motorized Lens, Field of View H: 114°–32°; V: 58°–17°; D: 138°–36° Smart H.265+; Smart H.264+; AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object; smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 ( Less false alarm, longer detection distance ) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, Roi, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB</p>	 <p>257,100,000</p>
<p>11 DH-IPC-HFW4431TP-S-S4</p>	<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265&amp;H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>	 <p>103,100,000</p>
<p>12 DH-IPC-HFW3849T1-AS-PV-S3</p>  	<p>8MP Smart Dual Illumination Active Deterrence Fixed-focal Bullet WizSense Network Camera 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 8 MP (3840 × 2160)@25/30 fps Min. Illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm illuminator, and the max. illumination distance: 30 m Intrusion, tripwire (support the classification and accurate detection of vehicle and human) WDR (120dB), 3D NR, HLC, BLC, digital watermarking, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256G SD card; built-in dual MICs; 1-ch speaker 12 VDC/PoE power supply, IP67 protection, Sound and light alarm (red and blue lights) SMD 3.0, One-click arming/disarming through alarm input Full Metal Case</p>	 <p>223,700,000</p>
<p>13 IPC-HFW3849T1-AS-PV-S4</p>  	<p>8MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 8 MP (3840 × 2160)@25/30 fps, H.265 codec, high compression rate, ultra-low bit rate Min. Illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m IVS: Intrusion, Tripwire, SMD 4.0, Quick Pick, Ai SSA, Ai Coding, WDR 120db, SSA, HLC, BLC, 3D DNR, Defog, AWB, AGC, Roi, ICR, Smart Illumination Dual Built-in Mic , Built-in Speaker, Audio in/out 1/1, Alarm Input 1 channel in: 5mA 3V–5 VDC, Alarm Output 1 channel out: 300mA 12 VDC ,Micro SD 256G, support two-way talk Power Supply 12V DC/PoE (802.3af), IP67 protection, One-tap arming/disarming through alarm input, Sound and light alarm (red and blue lights) Full Metal Case</p>	 <p>225,200,000</p>
<p>14 DH-IPC-HFW3449EP-AS-LED-3.6</p> 	<p>4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE Full Metal Case</p>	 <p>125,400,000</p>










<p>15 DH-IPC-HFW3449EP-AS-LED-2.8</p> 	<p>4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688x1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE Full Metal Case</p>		<p>125,400,000</p>
<p>16 HFW3441TP-ZS-27135</p> 	<p>4MP IR Vari-focal Bullet WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm-13.5 mm Motorized lens 25/30fps@4Mp(2688x1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE Full Metal Case</p>		<p>175,800,000</p>
<p>17 IPC-HFW2849S-S-IL</p>   	<p>8MP Smart Dual Light 2.8mm Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps Min. Illumination 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warmlight distance is 30m WDR 120db, BLC, HLC, AWB, AGC, RoI, 3D DNR, ICR, Smart Illumination IVS: Intrusion, Tripwire, SMD Plus, Smart Search Built-in Mic, Micro SD 256GB 12 VDC/PoE (802.3af), IP67 Protection, Full Metal Case</p>		<p>132,800,000</p>
<p>18 IPC-HFW2841T-ZS</p> 	<p>8MP IR Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" Progressive CMOS image sensor 8MP@20fps, @25/30fps, 2.7-13.5mm Motorized Lens Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) 0.0008 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on) Built-in IR LED, and the max. illumination distance is 60 m WDR 120db, BLC, HLC, AWB, AGC, RoI, 3D DNR, ICR, Smart Illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB, 12 VDC/PoE, IP67, IK10, Full Metal Case</p>		<p>210,800,000</p>
<p>19 IPC-HFW2549TL-S-PV</p>    	<p>5MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" Progressive CMOS, max. 5MP@20fps/4MP@25/30fps, 3.6 mm: H: 91.9°; V: 48.7°; D: 107.7° Min. Illumination 0.006 lux@F1.0 (Color, 30 IRE) 0.0006 lux@F1.0 (B/W, 30 IRE) 0 lux (Illuminator on) WDR 120 db, BLC, HLC, 3D DNR, RoI, AWB, AGC, Smart Dual Light 30m SMD+, Intrusion, tripwire, Active Deterrence, MSD 256GB, Built-in Mic &amp; Speaker, two-way talk, Sound and light alarm, One-tap arming/disarming IP67, 12 VDC/PoE, easy for installation, Metal Case</p>		<p>113,900,000</p>
<p>20 IPC-HFW2549T-AS-IL</p>   	<p>5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" Progressive CMOS image sensor 5MP(2960 × 1668)@20fps, (2688 × 1520)@25/30 fps Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Focal Length 2.7 mm-13.5 mm Min. Illumination 0.007 lux@F1.6 (Color, 30 IRE) 0.0007 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m WDR, RoI, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, IK10, Metal Case</p>		<p>145,500,000</p>
<p>21 IPC-HFW2541T-AS-S2</p>  	<p>5MP IR Fixed-focal Bullet WizSense Network Camera 3.6mm Lens, 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments Built-in IR LED, and the max. illumination distance is 80 m Min. Illumination, 0.007 Lux@F1.6 (Color, 30 IRE), 0.0007 Lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, Auto ICR Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human), SMD Plus Alarm: 1 in, 1 out; audio: 1 in, 1 out; Supports max. 256 G Micro SD card; built in MIC 12 VDC/PoE power supply, easy for installation, IP67, Metal Case</p>		<p>134,900,000</p>
<p>22 IPC-HFW2449S-S-LED</p>   	<p>4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination :0.005 lux@F1.0 Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus.Full Metal Case</p>		<p>93,500,000</p>










23	  	<p>4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera            4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image            Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps            H.265 codec, high compression rate, ultra-low bit rate            Min. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on)            Built-in warm light/IR LED, the max. illumination distance is 30 m            ROI, SMART H.264+/H.265+, flexible coding            Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking            Intrusion, tripwire (support the classification and accurate detection of vehicle and human)            Supports max. 256 G Micro SD card, <b>built in MIC</b>            12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus. Full Metal Case</p>			93,500,000
24	 	<p>4MP IR Fixed-focal Bullet WizSense Network Camera            4-MP 1/2.9" Progressive CMOS image sensor, Outputs 4MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps            Min. Illumination 0.006 Lux@F1.6(Color,30IRE) 0.0006 Lux@F1.6(B/W,30IRE) 0 lux (Illuminator on)            H.265 codec, high compression rate, ultra-low bit rate            Built-in IR LED, and the max. illumination distance is 30m            ROI, SMART H.264+/H.265+, WDR 120db, 3D NR, HLC, BLC, AWB, AGC, 3D DNR            Intelligent monitoring: Intrusion, tripwire, SMD            Micro SD card 256GB, built-in MIC, 12 VDC/PoE, IP67, Metal Case</p>			81,300,000
25	  	<p>4MP IR Vari-focal Bullet WizSense Network Camera            Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 ,(2560 × 1440)@25/30 fps            Min. Illumination, 0.008 lux@F1.5 (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux (Illuminator on)            H.265 codec, high compression rate, ultra-low bit rate, Focal Length 2.7 mm–13.5 mm            Built-in IR LED, and the max. illumination distance is 60 m            ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC            Intrusion, tripwire (support the classification and accurate detection of vehicle and human)            Alarm: 1 in, 1 out (Only - ZAS supports), audio: 1 in, 1 out (Only - ZAS supports), 256G SD card, <b>built in MIC</b>            12 VDC/PoE power supply, easy for installation, IP67, IK10 (optional) protection, SMD Plus</p>			157,600,000
26	 	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera            4MP, 1/3" Progressive CMOS            low illuminance 0.004 Lux@F1.0            high image definition 4MP@25/30fps, 3.6mm Fixed lens            SMART H.264+/H.265+, IVS Intrusion/Tripwire            WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch            Micro SD 256GB, Built-in Mic            12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>			86,100,000
27	 	<p>5-MP 1/2.7" CMOS image sensor, low luminance, Smart Dual Illumination            Min. Illumination : 0.003 lux@F1.0 (Color, 30 IRE) / 0.0003 lux@F1.0 (B/W, 30 IRE) / 0 lux (illuminator on)            Lens Fixed-focal 3.6 mm , 15.6 m Recognize &amp; 7.8 m Identify,            Illumination Distance : 30 m (2 IR LED) / 30 m (2 warm light)            AI H.265, AI H.264 , Smart H.265+, Smart H.264+, <b>Built-in MIC</b>            Main stream: 2880 × 1620 or 2960 × 1668 @20fps / 2688 × 1520 @30 fps            WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination, Defog, Scene Self-adaption            Storage : FTP, SFTP, Micro SD card (support max. 256 G), NAS            ROM : 128MB, RAM : 512MB, S/N Ratio &gt; 56db , Sound and Light Alarm,            Active Deterrence, IVS (Tripwire, intrusion), SMD 4.0, Smart Search, Quick Pick, AI SSA            Audio In/out : 1/1 , Alarm in/out : 1/1, RJ-45 (10/100 Base-T) , 3.3 W (12 VDC); 4.4 W (PoE), IP67</p>			188,500,000
28	 	<p>5MP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera            5MP, 1/2.7" CMOS image sensor            low illuminance 0.003 Lux@F1.0            5MP@20 fps, 4MP@25/30 fps, 3.6mm Fixed lens            SMART H.264+/H.265+, IVS Intrusion/Tripwire            WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch            Micro SD 256GB, Built-in Mic            12V, PoE, IP67, Built-in warm light, max. illumination distance: 30 m, Onvif Profile S/G/T, Full Metal Case</p>			140,500,000
29	 	<p>5MP IR Vari-focal Bullet WizSense Network Camera            5MP, 1/2.7" Progressive CMOS            0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on)            high image definition 5MP@20fps            2.7-13.5mm Motorized Lens            SMART H.264+/H.265+ 3 Streams            IVS Intrusion, Tripwire, Accurate Human/Vehicle Classification, SMD Plus            Micro SD 256GB            WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch            12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>			210,000,000
30		<p>5MP Lite IR Fixed-focal Bullet Network Camera            5MP, 1/2.7" Progressive CMOS            low illuminance 0.008 Lux@F1.6            high image definition 5MP@20fps, 3.6mm fixed Lens            SMART H.264+/H.265+, IVS Intrusion/Tripwire            1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB            WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch            12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T</p>			121,900,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
31	<p><b>Full-color</b></p> <p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera            2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)            Outputs max. 2 MP (1920 × 1080)@25/30 fps, Fixed Lens 3.6mm            Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B            Built-in warm light/IR LED : 30m/30m            ROI, WDR, 3D NR, HLC, BLC, digital watermarking            SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human)            Supports max. 256 G Micro SD card, built in MIC.            12 VDC/PoE power supply, easy for installation, IP67</p> <p><b>STARLIGHT</b> <b>WizSense</b></p>		75,900,000
32	<p><b>Full-color</b></p> <p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera            2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)            Outputs max. 2 MP (1920 × 1080)@25/30 fps, Fixed Lens 3.6mm            Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B            Built-in warm light/IR LED : 30m/30m            ROI, WDR, 3D NR, HLC, BLC, digital watermarking            SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human)            Supports max. 256 G Micro SD card, built in MIC.            12 VDC/PoE power supply, easy for installation, IP67</p> <p><b>STARLIGHT</b> <b>WizSense</b></p>		75,900,000
33	<p>2MP WDR IR Bullet Network Camera, starlight            1/2.8" 2Megapixel progressive CMOS            Min. Illumination:0.002 Lux@F1.6            Outputs max. 2MP (1920 × 1080) @25/30 fps, 3.6mm Fixed lens            SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion)            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB            Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p> <p><b>STARLIGHT</b></p>		57,600,000
34	<p>2MP IR Bullet Network Camera            1/2.7" CMOS image sensor, low illumination, high image definition            H.265+/H.265/H.264+/H.264 Double-stream encoding            25/30fps@1080P(1920x1080)            DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI            3.6mm, Max. IR LEDs Length 30m, Smart IR            Micro SD card memory 128 GB, IP67, PoE, AVI(Tripwire Intrusion)</p> <p><b>STARLIGHT</b></p>		55,600,000
35	<p>2MP Lite Full-color Fixed-focal Bullet Network Camera            1/2.8" CMOS image sensor, Outputs max. 2MP (1920 × 1080) @25/30 fps            ROI, SMART H.264+/H.265+, flexible coding,            Min Illumination 0.0017 Lux@F1.0            Intelligent detection: Intrusion, tripwire            WDR(120db), 3D NR, HLC, BLC, digital watermarking            Supports max. 256 GB Micro SD card and built-in Mic,12V DC/PoE ,IP67</p> <p><b>Full-color</b></p>		69,100,000
36	<p><b>Dual LIGHT</b></p> <p>8MP Entry Smart Dual Light Fixed-focal Bullet Network Camera            8-MP 1/2.7" Progressive CMOS sensor, 8MP@20 fps, and 4MP@25/30 fps, 3.6mm Fixed Lens, HFoV 100°            Built-in Multi-core Light, IR 30m warmlight 30m, 0.008 lux@F1.6 (Color, 30 IRE); 0.0008 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on)            Human Detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic            DWDR, HLC, BLC, 3D DNR, ROI, AGC, AWB            12VDC, IP67, Metal Case, easy for installation</p> <p><b>STARLIGHT</b> <b>Full-color</b></p>		113,100,000
37	<p><b>Dual LIGHT</b></p> <p>6MP Entry Smart Dual Light Fixed-focal Bullet Network Camera            1/2.7" Progressive CMOS sensor, max. 6MP@20 fps, and 4MP@25/30 fps, 3.6mm Fixed Lens, HFoV 91°            Built-in Multi-core Light, IR 30m warmlight 30m, 0.007 lux@F1.6 (Color, 30 IRE); 0.0007 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on)            DWDR, HLC, BLC, 3D DNR, ROI, AGC, AWB            Human Detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic            12VDC, IP67, Metal Case, easy for installation</p> <p><b>STARLIGHT</b> <b>Full-color</b></p>		80,100,000
38	<p>5MP 1/2.7" CMOS image sensor            Outputs max. 5MP (2880 × 1620) @20 fps, Fixed-focal 3.6mm            min illumination 0.003 Lux@F2.0 (B/W, 30 IRE)            H.265 codec, SMART H.264 +/-H.265+,            Built-in IR LED, and the max. illumination distance is 30 m            DWDR, 3D NR, HLC, BLC, digital watermarking            Built-in MIC, IP67, POE</p> <p><b>STARLIGHT</b></p>		74,200,000
39	<p><b>Dual LIGHT</b></p> <p>4MP Entry Full-color Fixed-focal Bullet Network Camera            -MP 1/2.9" Progressive CMOS sensor, max. 4MP@25/30 fps, 3.6mm Fixed Lens, HFoV 95°            IR 40m, Warmlight 30m, 0.006 lux@F1.6            WDR 120db, HLC, BLC, 3D DNR, ROI, AGC, AWB            human detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic            12 VDC/PoE, Metal + plastic, IP67</p> <p><b>STARLIGHT</b> <b>Full-color</b></p>		73,900,000
40	<p>4MP Entry Full-color Fixed-focal Bullet Network Camera            4-MP 1/3" Progressive CMOS image sensor, Outputs max. 4 MP (2560 × 1440)@25/30 fps            Min. Illumination 0.008 lux@F1.6, Illumination Distance 15 m (49.21 ft) (warm light)            SMART H.264+/H.265+, ROI, WDR 120db, BLC, HLC, AWB, AGC, 3D DNR, Smart Illumination            Built-in Mic, 12 VDC/PoE, Metal + plastic, IP67</p> <p><b>Full-color</b></p>		69,700,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
41	<p><b>NEW</b></p> <p>2 MP Entry Full-color Fixed-focal Bullet Network Camera 2-MP 1/2.8" Progressive CMOS, max. 2 MP (1920 × 1080)@25/30 fps warm light 30m, 0.005 lux@F1.6, 3.6 mm: H: 87°; V: 44°; D: 105° DWDR, 3D NR, HLC, BLC, ROI, AWB, AGC, SMART H.264+/H.265+ human detection, Full-color IP67, 12 VDC/PoE, easy for installation, Metal+Plastic</p>		53,500,000
42	<p>2MP Smart Dual Light Fixed-focal Bullet Network Camera 2-MP 1/2.8" Progressive CMOS sensor, max. 2MP@30 fps Built-in multi-core light, IR 30m Warmlight 30m, 0.005 lux@F1.6 (Color,30 IRE) DWDR, HLC, BLC, AGC, AWB, 3D DNR, Smart Dual Light human detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic 12 VDC/PoE, Metal + plastic, IP67</p>		55,300,000
43	<p>2MP Entry Full-color Fixed-focal Bullet Network Camera 2-MP 1/2.8" Progressive CMOS sensor, max. 2MP@25/30 fps, 2.8mm Fixed Lens, HFoV 107° H.265 codec, high compression rate, ultra-low bit rate, 0.005 lux@F1.6, Warmlight 15m DWDR, 3D DNR, HLC, BLC, AWB, AGC, ROI Built-in MIC IP67, 12 VDC/PoE, Metal+Plastic</p>		52,500,000
44	<p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T</p>		51,500,000
45	<p>5MP IR Vari-focal Vandal-proof Dome WizMind Network Camera 5-MP (2960 × 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (Illuminator on 40m) 2.7 mm-13.5 mm Motorized Lens, Field of View H: 114°-32°; V: 58°-17°; D: 138°-36° Smart H.265+; Smart H.264+, AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object; smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 ( Less false alarm, longer detection distance ) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, Roi, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB IP67 and IK10 protection</p>		289,800,000
46	<p>5MP IR Fixed-focal Dome WizSense Network Camera 5-MP (2960 × 1668) @20fps 1/2.7" CMOS image sensor, excellent low luminance performance and high definition of images 0.005 lux@F1.4 (Color, 30 IRE), 0.0005 lux@F1.4 (B/W, 30 IRE), 0 lux (Illuminator on 50m) 2.8 mm: Horizontal: 111°; Vertical: 58°; Diagonal: 132° Smart H.265+, Smart H.264+, AI Coding IVS: Tripwire, Intrusion, SMD 4.0, Smart Search, Scene Changing, Audio Detection BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, Roi, Defog, AFSA Built-in Mic, Micro SD up to 256GB, ROM 128MB, RAM 512MB IP67, IK10 protection, Easy Installation</p>		131,600,000
47	<p>4MP IR Fixed focal Dome WizSense Network Camera 1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520)@30 fps H.265 codec, SMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking Supports max. 256 G Micro SD card, 12V DC/POE, IP67, IK10, SMD Plus Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE) Audio Input 1 channel (RCA port), Audio Output 1 channel (RCA port) Alarm Input 1 channel in, Alarm Output 1 channel out</p>		108,500,000
48	<p>4MP Full-color Fixed-focal Eyeball Wizsense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, 4MP(2688× 1520)@20fps, (2560×1440)@25/30fps Min. Illumination 0.005 lux@F1.0, Built-in warm light, max. illumination distance 30m Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Roi, WDR 120db, HLC, BLC, AGC, AWB, 3D DNR, Smart illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, Metal+Plastic Case</p>		93,200,000

49	DH-IPC-HDW2449T-S-IL		<p>4MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps Min. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human Supports max. 256 G Micro SD card; built in MIC, 12 VDC/PoE power supply, easy for installation, IP67 protection,SMD Plus</p>		94,700,000
50	IPC-HDW2439TP-AS-LED-0360B		<p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 3.6mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, <b>Built-in Mic</b> 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		88,100,000
51	IPC-HDW2439TP-AS-LED-0280B-S2		<p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, <b>Built-in Mic</b> 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		88,100,000
52	DH-IPC-HDBW2441E-S		<p>4MP 1/2.9" CMOS image sensor, IR Fixed-focal Dome WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2566 × 1440@25/30 fps Min. Illumination 0.008 lux@F1.6 (Color,30IRE), 0.0008 lux@F1.6 (B/W,30IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card; <b>built in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67, IK10 protection, SMD Plus</p>		87,500,000
53	DH-IPC-HDBW2441R-ZS		<p>4MP IR Vari-focal Dome WizSense Network Camera, 4-MP 1/2.9" CMOS image sensor Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440, (2560 × 1440)@25/30 fps Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance : 40 m, ROI, SMART H.264+/H.265+ WDR 120dB, 3D NR, HLC, BLC, Focal Length 2.7 mm-13.5 mm Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); 256G SD card; <b>built in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67 and IK10 protection, SMD Plus</p>		153,500,000
54	IPC-HDW2441T-S		<p>4MP IR Fixed-focal Eyeball WizSense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, Output 4MP (2688 × 1520)@20 fps, 2560 × 1440@25/30 fps Min. Illumination 0.006 lux@F1.6 (Color, 30IRE) 0.0006 lux@F1.6 (B/W, 30IRE) 0 lux (Illuminator on) Smart H.265+; Smart H.264+, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m WDR 120db, 3D NR, HLC, BLC, ROI, AWB, AGC, 3D DNR Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB, IP67, 12 VDC/PoE, Metal+Plastic</p>		82,600,000
55	HDBW2431RP-ZS-27135-S2		<p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>		135,200,000
56	IPC-HDW1639T-A-IL		<p>6MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera 1/2.7" Progressive CMOSsensor, max. 6MP@20 fps, and 4MP@25/30 fps, 2.8mm Fixed Lens, HfVv 110° Built-in Multi-core Light, IR 30m warmlight 30m, 0.007 lux@F1.6 (Color, 30 IRE); 0.0007 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on) DWDR, HLC, BLC, 3D DNR, ROI, AGC, AWB Human Detection, 2 Streams, H.265+, Smart Codec, Smart Dual Light, Built-in Mic 12VDC, IP67, Metal Case, easy for installation</p>		80,100,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
57	HDBW1431EP-0280B-S4 4MP Entry IR Fixed-focal Dome 1/3" CMOS image sensor Network, low illuminance Min. illumination : 0.03 Lux @ F2.0 ,illumination Distance : 30 m(3 IR LED), S/N Ratio > 56db Lens Fixed-focal 2.8 mm , Horizontal: 93° / Vertical: 53° / Diagonal: 111° Smart H.265+, H.265, Smart H.264+, H.264 Main Stream: 2688 × 1520 (20 fps) , high compression rate, ultra-low bit rate WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI(4 years), Smart Illumination Storage(FTP, SFTP, NAS) , ROM : 128MB, RAM : 512MB 12V DC/PoE (802.3af), Power Consumption < 5.5W, 1 port RJ-45 (10/100 Base-T) ,IP67, IK10		70,100,000
58	HDW1431T1P-A-0360B-S4 4MP Entry IR Fixed-focal Eyeball Network Camera 1/3" 4Megapixel progressive CMOS, Fixed-focal 3.6mm 20fps@4.1M(2688x1520) & 25fps@4M(2560x1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), Image flip, 3D DNR, HLC, BLC, digital watermark Support ROI,Built-in MIC Max. IR LEDs Length 30m, IP67, PoE		70,030,000
59	HDW1431T1P-0280B-S4-S5 4MP Entry IR Fixed-focal Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 20fps@4.1M(2688x1520) & 25fps@4M(2560x1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE		64,100,000
60	DH-IPC-HDW2249TP-S-IL-0280B 2MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance Min. illumination : 0.0002 lux@F1.6 (B/W, 30 IRE) , Fixed Lens 2.8 mm Outputs max. 2 MP (1920 × 1080)@25/30 fps Smart Codec : Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B SMD Plus, Intrusion, tripwire (accurate detection of vehicle and human). Supports max. 256G Micro SD card, <b>built in MIC</b> . ROI, WDR, 3D NR, HLC, BLC, digital watermarking Built-in warm light/IR LED : 30m/30m 12 VDC/PoE power supply, easy for installation, IP67		76,100,000
61	HDW2231TMP-AS-S2 2MP WDR IR Eyeball Network Camera, <b>Starlight</b> 1/2.8" 2Megapixel progressive CMOS Min. illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		65,000,000
62	IPC-HDW2231TP-AS-0280B-S2 2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.002 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		63,900,000
63	IPC-HDW2230T-AS-S2 2MP IR Eyeball Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005 Lux @ F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion, Tripwire Micro SD 256GB, Built-in Mic DWDR, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T		55,500,000
64	IPC-HDBW2230E-S-S2 2MP Lite IR Fixed-focal Dome Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005" Lux @F1.6 high image definition 2MP@25/30fps 2.8mm Fixed Lens SMART H.264+/H.265+ IVS Tripwire; intrusion Micro SD 256GB DWDR, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T		55,200,000
65	HDW1530TP-0280B-S6 5MP Entry IR Fixed-focal Eyeball Network Cam 1/2.7" CMOS image sensor low illuminance 0.003 Lux @F2 Outputs max. 5MP (2880 × 1620) @20 H.265 code, SMART H.264 +/H.265 DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC,12 V DC/PoE power supply		75,500,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
66	<p><b>Dual LIGHT</b></p> <p><b>NEW</b></p> <p>4MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera            4-MP 1/2.9" Progressive CMOS, max. 4 MP (2560 × 1440)@25/30 fps, 2.8 mm: H: 94°; V: 52°; D: 111°            Min. Illumination 0.006 lux@F1.6 (Color, 30 IRE) 0.0006 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)  <b>Human Detection</b>, Smart Dual Light 30m, <b>Built in Mic</b>, easy for installation            WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, ROI, SMART H.264 +/H.265+            IP67, 12 VDC/PoE, Metal+plastic</p> <p><b>STARLIGHT Full-Color</b></p>		74,900,000
67	<p><b>Dual LIGHT</b></p> <p><b>NEW</b></p> <p>2MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera            2-MP 1/2.8" Progressive CMOS, max. 2MP@25/30fps, 2.8 mm: H: 103°; V: 55°; D: 123°            Min. Illumination 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (Illuminator on)            DWDR, 3D NR, HLC, BLC, AWB, AGC, ROI, SMART H.264+/H.265+  <b>Human Detection</b>, Smart Dual Light 30m, Built-in Mic            IP67, 12 VDC/PoE, Metal + Plastic</p> <p><b>STARLIGHT Full-Color</b></p>		56,100,000
68	<p><b>STARLIGHT Full-Color</b></p> <p>2MP Lite Full-color Fixed-focal Eyeball Network Camera            Outputs max. 2MP (1920 × 1080) @25/30 fps            H.265 codec, high compression rate, ultra-low bit rate            Min. Illumination : 0.005 Lux @F1.6,            Built-in LEDs, max LED distance: 15 m, <b>built in MIC</b>            ROI, SMART H.264/H.265, flexible coding, applicable to various            Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking,            12V DC/PoE power support, IP67 protection</p>		55,100,000
69	<p><b>STARLIGHT Full-Color</b></p> <p>2 MP Entry Full-color Fixed-focal Bullet Network Camera            2MP, 1/2.8" Progressive CMOS            low illuminance 0.005 Lux @F1.6            high image definition 2MP@25/30fps            3.6mm fixed lens            Smart H.265+/Smart H.264+            DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination            12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>		49,400,000
70	<p><b>STARLIGHT Full-Color</b></p> <p>2 MP Entry Full-color Fixed-focal Bullet Network Camera            2MP, 1/2.8" Progressive CMOS            low illuminance 0.005 Lux @F1.6            high image definition 2MP@25/30fps            2.8mm fixed lens            Smart H.265+/Smart H.264+            DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination            12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>		49,400,000
71	<p>1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom            H.264+/H.264 Encoding            Max. 25/30fps@1080P, 25/30/50/60fps@720P            WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max 100°/s pan speed, 360° endless pan rotation            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion   Scene Change   Face   Abandoned-Missing Object)</p>		133,000,000
72	<p><b>STARLIGHT</b></p> <p>1/2.8" 2MP STARVIS™ CMOS (Starlight)            H.265+/H.265/H.264+/H.264 Triple-streams encoding            Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom            WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max Pan: 80° /s; Tilt: 40° /s speed            Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE            (Tripwire Intrusion Abandoned/Missing Face Detection)</p>		137,000,000
73	<p><b>Wiz Sense</b></p> <p>2MP Starlight IR AI WizSense Network PTZ Camera            H.265; H.264B; H.264M; H.264H; MJPEG; MJPEG (Sub Stream); H.265+; H.264+            Focal Length 2.7 mm–13.5 mm, Optical Zoom 5x            Tripwire and intrusion, Deep-learning-based perimeter protectionm SMD Plus            IR distance up to 30m            Starlight technology            Up to 300 presets            DWDR, HLC, BLC, AGC, AWB, 2D/3D DNR, Day/Night Auto (ICR), Rol, Defog            Built-in Mic, Built-in Speaker, Two Way Audio            ONVIF Profile S&amp;G&amp;T; CGI            IP66; TVS 2000V lightning proof; surge protection; voltage transient protection</p>		180,000,000
74	<p><b>Wiz Sense</b></p> <p>2MP 45x Starlight IR WizSense Network PTZ Camera            1/2.8" 2Megapixel STARVIS™ CMOS            H.265; H.265+; H.264+; H.264; MJPEG (Sub Stream)            Max. 50/60 fps@1080P            Pan/Tilt Range Pan: 0°–360°; Tilt: -15°–+90°            Manual Control Speed Pan: 0.1°/s–240°/s; Tilt: 0.1°/s–120°/s            WDR(120dB), HLC, BLC, 2D/3D DNR, Rol, EIS, Defog, AWB, AGC, Privacy Masking, Day/Night Auto            Auto Tracking, SMD Plus, Intrusion, Tripwire, Object Abandoned/Missing, Face Detection            Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan            Alarm I/O 2/1, Audio I/O 1/1, Supports Two Way Talk            Focal Length 3.95 mm–177.7 mm, Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux (IR on)            IR distance up to 150 m, 45x optical zoom            ONVIF Profile S&amp;G&amp;T, DC 24V/2.5A ± 25%; PoE+ (802.3at), Operating Temperature -40°C to +70°C            IP67; IK10; TVS 6000V lightning protection; surge protection; voltage transient protection</p>		891,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
75	DH-SD5A232XB-HNR	<p>2MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS 32x optical zoom, Max. 50/60 fps@2M Min Illumination Color: 0.005 lux@F1.6, Focal Length 4.8 mm~154 mm Smart H.265+; H.265; Smart H.264+; H.264B Face detection, tracking and perimeter protection, SMD PLUS IR distance up to 150 m, PoE+, IP67, IK10 WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC</p>		770,000,000
76	DH-SD5A232XA-HNR	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 4.9mm~156mm 32x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR(2D/3D), BLC, HLC Support Defog, ROI, Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection) Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm 2/1 in/out, Audio 1/1 in/out IR Distance up to 150m, PoE+, IP67, IK10</p>		770,000,000
77	DH-SD49425ZB-HNR	<p>4MP 25x Starlight IR WizSense Network PTZ Camera, Image Sensor: 1/2.8" STARVIS™ CMOS 1/2.8" 4Megapixel CMOS, Powerful 25x optical zoom, ROM: 4GB, RAM: 1GB Starlight technology, Max.25/30fps@4M, Illuminator Number: 4 Focal Length: 4.8 mm~120 mm, Field of View: H: 60.0°~2.5°; V: 30.8°~2.2°; D: 66.7°~2.9° Min. Illumination: Color: 0.005Lux@F1.6, B/W: 0.0005Lux@F1.6: 0Lux@F1.6 (IR light on) Illuminator On/Off Control: Zoom Prio/Manual/SmartIR Perimeter protection, Face Detection, Smart Capture, SMD PLUS, IVS: Object Abandoned/Missing Support PoE+, IR distance up to 100m, BLC, WDR 120db, HLC, AGC, ANR, ROI, Electronic Defog Pan: 0.1°~200°/s, Tilt: 0.1°~120°/s, Presets: 300, Tour: 8 (up to 32 presets per tour), Pattern: 5, Scan: 5 IP66, DC 12V/3A, PoE+ (802.3at) Audio Input: 1, Audio Output: 1, Alarm I/O: 2/1</p>		507,000,000
78	SD49425XB-HNR	<p>4MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" STARVIS™ Progressive CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max.25/30fps@4M, 960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		507,000,000
79	SD49225XA-HNR-S3	<p>2MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS , 25x optical zoom, Min Illumination Color: 0.005 lux@F1.6 Max. 25/30 fps@1080p IR distance up to 100 m , Perimeter protection, Face detection, SMD Plus, IP66 Pan: 0° to 360° endless , Tilt: -15° to +90° , auto flip 180° , Pan: 200°/s; Tilt: 100°/s Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub Stream) Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC</p>		414,000,000
80	SD49225XA-HNR	<p>2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P, 960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		414,000,000

81	SD49225DB-HNY	<p>2MP 25x Starlight IR Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm–120 mm Max. 25/30 fps@1080p Min. Illumination Color: 0.005 lux@F1.6 B/W; 0.0005 lux@F1.6 0 lux (IR light on) Illumination Distance 100 m (328.08 ft) (IR) Max. Aperture F1.6–F3.5 Smart IR - 4 IR - S/N Ratio <math>\geq</math> 55 dB IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+;H.265;Smart H.264+;H.264;H.264B;MJPEG(Sub Stream) WDR 120db, Day/Night Auto (ICR)/Color/B/W, HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, Rol, EIS, Defog Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, 12 VDC/3 A, PoE+, IP66, FTP/ Micro SD card (512 GB)/ NAS</p>		414,000,000
82	SD49425GB-HNR	<p>4MP 25x Starlight IR Network PTZ Camera 1/2.8" STARVIS™ CMOS 25x optical zoom, Focal Length 5 mm–125 mm Starlight technology, Min. Illumination Color: 0.005 lux@F1.6 B/W; 0.0005 lux@F1.6 0 lux@F1.6 (IR light on) Max. 25/30fps@4M. IR distance up to 100 m Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Perimeter protection, Face detection, SMD 4.0, Acupick IP66, Audio I/O 1/1, Alarm I/O 2/1</p>		507,000,000
83	SD5A432XB-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.6, 0 Lux (IR on) 4.8 mm–154 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Support human, motor vehicle and non-motor vehicle image capture Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) Support filtering false alarms caused by animals, rustling leaves, bright lights, etc. Pan: 0° to 360° endless , Tilt: -15° to +90°, auto flip 180° , Pan: 0.1°–300°/s , Tilt: 0.1°–200°/s WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Alarm I/O : 2/1 , Audio I/O : 1/1 , PoE+ ,IP67; IK10; TVS 6000 V</p>		834,000,000
84	DH-SD5A432GB-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera Image Sensor 1/2.8" CMOS, Max. Resolution 2560 (H) x 1440 (V) Electronic Shutter Speed 1/1 s–1/30,000 s, Min. Illumination, Color: 0.005 lux@F1.6, B/W: 0.0005 lux@F1.6 Illumination Distance 150 m(IR), Focal Length 4.8 mm–154 mm Manual Control Speed Pan: 0.1°/s–300°/s, Tilt: 0.1°/s–200°/s Preset 300, Tour 8 (up to 32 presets per tour), Pattern 5, Scan 5 Perimeter Protection, Face Detection, Auto Tracking, Quick Pick, SMD BLC, WDR 120 db, WB, AGC, ANR, Rol, EIS, Defog Electronic, S/N Ratio <math>\geq</math>55 dB Storage : FTP, Micro SD card (512 GB); NAS, Alarm I/O 2/1, Audio I/O 1/1 Power Supply 24 VDC, 2.5 A (<math>\pm</math> 25%), Operating Temperature -40 °C to +70 °C</p>		872,000,000
85	SD5A432XA-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on) 4.9 mm–156 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection; voltage transient protection</p>		812,000,000
86	SD5A445GB-HNR	<p>4MP 45x Starlight IR Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.264H; H.264B; Smart H.265+; H.264; H.265; MJPEG(Sub Stream); Smart H.264+ Min. Illumination Color: 0.005 lux@F1.6 B/W; 0.0005 lux@F1.6 0 lux (IR light on) 3.95 mm–177.75 mm 45x optical zoom Starlight technology IR distance up to 150 m WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Perimeter protection, Face detection, SMD 4.0, Quick Pick, Auto-tracking 3.0 Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, IP67, IK10, TVS 6000V lightning proof; surge protection; voltage transient protection</p>		1,040,000,000




87		<p>4MP 45x Starlight IR DHOP Network PTZ Camera - Max. 25/30 fps@4MP                      1/2.8" 4Megapixel STARVIS™ CMOS - Progressive CMOS - ROM : 4GB - RAM : 1GB                      1T computing power for enhanced performance - Flash : 350 M - Memory : 300 M                      Compression H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream)                      Min. Illumination Color: 0.005 Lux@F1.6 / B/W: 0.0005 Lux@F1.6 / 0 Lux (IR light on)                      Starlight technology - Illumination Distance : 150 m (492.13 ft) - Illuminator Number : 4                      Focal Length 3.95 mm-177.7 mm - Max. Aperture F1.6-F4.95 - Field of View H: 70.3°-1.8°; V: 37°-1°                      Pan: 0°-360°; Tilt: -15° +90° / Manual Control Speed : Pan: 0.1°/s-300°/s; Tilt: 0.1°/s-200°/s                      Preset Speed : Pan: 400°/s; Tilt: 300°/s - Presets : 300 - Tour 8 (up to 32 presets per tour) - Pattern : 5                      WDR(120), HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, ROI, EIS, Electronic Defog                      Alarm I/O 2/1 - Audio I/O 1 (Line in; bare wire)/1 (Line out; bare wire) - 1 RJ-45 Port 10/100Base-T                      DC 24 V/2.5 A ± 25% - PoE+ (802.3at), 11 W / 20 W (IR light on) IP67, IK10</p>		1,014,000,000	
 	88		<p>4MP 45x Starlight IR WizSense Network PTZ Camera                      1/2.8" 4Megapixel STARVIS™ Progressive CMOS                      H.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M                      Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on)                      3.95 mm-177.7 mm Powerful 45x optical zoom Max. Aperture F1.6-F4.95                      Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°-360° endless rotation                      WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR                      Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor                      vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering                      Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan                      Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T                      IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection</p>		1,014,000,000
 	89		<p>4MP 45x Starlight IR WizSense Network PTZ Camera                      1/2.8" 4Megapixel STARVIS™ Progressive CMOS                      H.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) Max. 25/30fps@4MP                      Minimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on)                      3.95 mm-177.75 mm Powerful 45x optical zoom Max. Aperture F1.6-F4.95                      Pan/Tilt Range Pan: 0°-360° endless; Tilt: -20°-90°,auto flip 180° Preset Speed Pan: 300° /s ; Tilt: 200° /s                      WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, Rol, EIS, Defog                      Deep-learning-based auto tracking and perimeter protection                      Face detection, SMD Plus, Tripwire, Intrusion. Human/Vehicle/Motor-non Motor Vehicle Detection                      Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan                      Micro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&amp;G&amp;T                      IR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10</p>		1,062,500,000
 	90		<p>4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live &amp; Playback                      Smart H.265+/Smart H.264+/H.265/H.264                      Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding.                      Up to 8MP Resolution for Preview &amp; Playback                      Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or                      2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS)                      Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P                      1 SATA 2.0 port, up to 8TB                      1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only                      1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		54,500,000
91		<p>8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live &amp; Playback                      Smart H.265+/Smart H.264+/H.265/H.264                      Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding.                      Up to 8MP Resolution for Preview &amp; Playback                      Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or                      2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS)                      Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P                      1 SATA 2.0 port, up to 8TB                      1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only                      1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		66,000,000	
92	 	<p>8CH Compact 1U 1HDD Lite Network Video Recorder                      Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG                      decoding capability: 6 × 1080p@30 fps                      Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth                      Supports IPC up to 12MP                      AI by Recorder supports 4-channel SMD                      AI by Camera supports perimeter protection and SMD                      Supports one-click arming and disarming                      1 HDMI, 1 VGA, Audio I/O 1/1(two way talk only), 1 SATA up to 20TB                      LAN 10/100, 12 VDC, 1.5 A</p>		91,800,000	
93		<p>8 Channel Lite Series, Compact 1U 1HDD Network Video Recorder                      Smart H.265+/H.265/Smart H.264+/H.264 decoding format                      Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding                      AI by camera: perimeter protection, and SMD Plus                      Multi-channel Playback Up to 8 channels, HDD Interface 1 SATA port, up to 16 TB                      Audio Input/Out : 1/1 , Network Port 1 × RJ-45, 10/100 Mbps                      Power Supply 12 VDC, 1.5 A</p>		87,700,000	

<p>94 NVR2108HS-I2</p> 	<p>8 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding 1-channel face detection and recognition (AI by NVR) 1-channel perimeter protection (AI by NVR), 4-channel SMD Plus (AI by NVR) AI by camera: Face detection and recognition, perimeter protection, and SMD Plus HDD 1 SATA port, up to 10 TB, RCA Input 1, RCA Output 1 Power Supply 12 VDC, 1.5 A, Operating Temperature -10 °C to +55 °C</p>		<p>110,000,000</p>
<p>95 NVR2116HS-I2</p> 	<p>16 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Network Bandwidth: AI off: Access: 144 Mbps; Storage: 144 Mbps; Forward: 72 Mbps AI on: Access: 72 Mbps; Storage: 72 Mbps; Forward: 36 Mbps Resolution: 12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1 Decoding Capability: AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 1 × VGA, 1 × HDMI (simultaneous) 4K Output 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR); AI by camera: Face detection and recognition, perimeter protection, and SMD Plus 1 SATA II port, up to 10TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		<p>136,500,000</p>
<p>96 DHI-NVR2216-I</p> 	<p>16 Channel 12MP WizSense NVR 1/4/9/16 Live &amp; Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding AI Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps AI Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 2 SATA 2.0 port, up to 8TB each, Total 16TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		<p>175,400,000</p>
<p>97 DHI-NVR2216-I2</p>	<p>16 Channel 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding AI by NVR: 1-channel face detection and recognition; 1-channel perimeter protection; up to 10 face databases and 5,000 face images; 4-channel SMD Plus AI by camera: Face detection and recognition, perimeter protection, and SMD Plus 2 SATA each up to 10TB, 2 USB, 1 HDMI, 1 VGA, 1 LAN 1000Mbps, Audio in/out 1/1, Onvif (S, T, G)</p>		<p>175,400,000</p>
<p>98 NVR4116HS-4KS3</p> 	<p>16CH Compact 1U 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps Max. 160/160/80 Mbps incoming/recording/outgoing bandwidth Supports IP cameras with a resolution up to 12 MP AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map Supports EPTZ, and one-click arming and disarming 1 SATA port up to 20 TB, 1 HDMI, 1 VGA Simultaneous/Heterogeneous, Audio I/O 1/1, Alarm I/O 2/1, 1000Mb LAN, ONVIF 22.12(Profile T; Profile S; Profile G)</p>		<p>132,200,000</p>
<p>99 NVR4216-4KS3</p> 	<p>16CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. 160/160Mbps incoming/recording bandwidth Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps HDMI(4K)/VGA simultaneous video output AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map Supports IP cameras with a resolution up to 12MP 2 SATA ports. Each disk up to 20TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p>		<p>176,200,000</p>

<p>100 NVR4232-EI</p>		<p>32CH 1U 2HDDs WizSense Network Video Recorder                      Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format                      Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled)                      Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding                      HDMI(4K)/VGA simultaneous &amp; Independent video output                      AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus                      AI by Camera: Face detection(8CHs) and recognition(8CHs), perimeter protection(8CHs); SMD Plus(8CHs); people counting; stereo analysis; heat map                      Supports IP cameras with a resolution up to 16MP                      2 SATA ports, up to 16TB., Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p>		<p>251,500,000</p>
<p>101 NVR4232-4KS3</p>		<p>32CH 1U 2HDDs Lite Network Video Recorder                      Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats                      Max. 160Mbps incoming bandwidth                      Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps                      HDMI(4K)/VGA simultaneous video output                      AI by Recorder supports 4-channel SMD Plus                      AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map                      Supports IP cameras with a resolution up to 12 MP                      2 SATA ports. Each disk up to 20TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p>		<p>213,000,000</p>
<p>102 NVR4432-EI</p>		<p>32CH 1.5U 4HDDs WizSense Network Video Recorder                      Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format                      Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled)                      Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding                      1 HDMI, 1 VGA, 4K, Simultaneous/heterogeneous                      AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus                      AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; ANPR; people counting; stereo analysis; heat map                      Supports IP cameras with a resolution up to 16MP                      4 SATA ports, up to 16 TB each, Audio I/O 1/1, Alarm I/O 16/4, 3 USB Ports, 2 1000Mb LAN                      ONVIF 22.06(Profile T; Profile S; Profile G)</p>		<p>424,800,000</p>
<p>103 NVR5232-EI</p>		<p>32 Channels 1U 2HDDs WizSense Network Video Recorder                      Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format                      Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps                      Max. 384 Mbps incoming/recording/outgoing bandwidth                      16ch AcuPick, N+M Clustering, Face Detection, Face Recognition, Face Attributes, Face Expression, SMD Plus, Perimeter Protection, Metadata, ANPR, Stereo Analysis, Heatmap, People Counting                      AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.                      AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting                      Audio in/out 1/1, Alarm in/out 4/2, 2 SATA each up to 16TB, RS232, RS485, 2 USB 2, 1 USB 3, 1 HDMI, 1 VGA, 1 LAN</p>		<p>404,900,000</p>
<p>104 NVR5432-EI</p>		<p>32 Channels 1.5U 4HDD WizSense Network Video Recorder                      Industrial-grade processor - Embedded Linux OS                      Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format                      Max. 384 Mbps incoming/recording/outgoing bandwidth                      AI by recorder: 2ch face detection and recognition, 4ch perimeter protection, and 8ch SMD Plus                      AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting                      Network Port 2 (10/100/1000 Mbps Ethernet port, RJ-45)                      4 SATA ports, up to 16 TB - Security baseline 2.3 - Supports 4K display - Alarm In/Out : 16ch/6ch</p>		<p>554,200,000</p>
<p>105 NVR5832-EI</p>		<p>32 Channels 2U 8HDD WizSense Network Video Recorder                      Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format                      Max. 384 Mbps incoming/recording/outgoing bandwidth                      Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps                      Support AcuPick with Max. 16-Channel, Support N+M cluster                      AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.                      AI by camera: Face detection(16CHs) and recognition(16CHs), perimeter protection(16CHs), SMD Plus(16CHs), metadata(8CHs), ANPR(8CHs), stereo analysis, heat map, and people counting                      Audio in/out 1/2 for Two way talk only, Alarm in/out 16/8, USB*3, HDMI*2, VGA*2, LAN*2*1000, eSATA*1, 8 SATA Ports each up to 20TB, RS-232, RS-485, P2P Support, Onvif (S/T/G)</p>		<p>843,000,000</p>



مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
106 NVR5464-EI	<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Industrial-grade processor - Embedded Linux Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Support AcuPick with Max. 16-Channel - Support N+M cluster - Support Raid0/1/5/6/10 Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2-ch face detection and recognition, 4-ch perimeter protection, and 8-ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Security baseline 2.3 - Alarm In/Out : 16/6 - 4 SATA ports, each disk up to 20 TB HDMI:2 - VGA:2 - USB:4 - RS485:2 - RS232:1</p>		701,000,000
107 NVR5864-EI	<p>64 Channels 2U 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Industrial-grade processor - Embedded Linux Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Support AcuPick with Max. 16-Channel - Support N+M cluster - Support Raid0/1/5/6/10 Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2-ch face detection and recognition, 4-ch perimeter protection, and 8-ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Security baseline 2.3 - Alarm In/Out : 16/8 - 8 SATA ports, each disk up to 20 TB HDMI:2 - VGA:2 - USB:4 - RS485:2 - RS232:1</p>		969,900,000
108 NVR5864H-XI	<p>64CH 2U 8HDDs WizMind Network Video Recorder Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG Max. decoding capability: 32 × 1080p@30 fps Max. 512/512/512 Mbps incoming/recording/outgoing bandwidth Supports IPC up to 32 MP, AcuPick with up to 36 channels, EPTZ, and one-click arming and disarming AI by Recorder supports 8-channel face detection and recognition, up to 20 face databases and 200,000 face images; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting RAID 0/1/5/6/10, N+M cluster, and iSCSI, HDD hot swapping 2 VGA, 2 HDMI, Audio I/O 1/1, Alarm I/O 16/8, 1 E-SATA, 8 SATA each up to 20TB total 160TB, 2x LAN 1000, USB:4 - RS485:2 - RS232:1</p>		1,362,000,000
109 DHI-NVR608H-32-XI	<p>32 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+, H.265; Smart H.264+, H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p>		1,269,900,000
110 DHI-NVR608H-64-XI	<p>64 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+, H.265; Smart H.264+, H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p>		1,795,000,000

111	NVR608H-128-XI		<p>128 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p>		2,520,000,000
112	NKB1000		<p>Keyboard to Control : Dahua High Speed Dome (all models) Dahua Standalone DVR , Dahua Network High Speed Dome Network Video Server, Connection : RS485, RS422, USB, RS232 &amp; Network Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour &amp; Pattern Control, On-Screen Menu &amp; User Operation Procedure Tips Connect to SmartPSS via USB</p>		227,900,000

